

## STANDARD CONSTRUCTION NOTES FOR STREET NAME SIGNS

- 1. ALL STREET SIGNS SHALL BE 3M DIAMOND GRADE DG3 DOUBLE-FACED EXTRUDED BLADES.
- 2. FIRST LETTER OF SUFFIX SHALL BE UPPERCASE WITH ALL REMAINING LETTERS TO BE LOWERCASE
- 3. ADDRESS NUMBERS FOR STREET NAME BLADES WILL BE PROVIDED AT A LATER DATE.
- 4. STREET SIGN POSTS SHALL BE 12 FEET LONG, 4 FEET DRIVEN INTO THE GROUND.
- 5. SIGN POSTS FOR STREET NAME BLADES SHALL BE ROUND TUBULAR ALUMINUM OR HOT DIPPED GALVANIZED STEEL, OUTSIDE DIAMETER 2-3/8 INCHES, WALL THICKNESS 0.109 INCHES.
- 6. ALL PUBLIC STEET NAME BLADES SHALL BE "GREEN" IN COLOR. LETTERING ON ALL STREET NAME BLADES SHALL BE HIGH INTENSITY, "WHITE" IN COLOR.



## STANDARD DETAILS

STREET NAME BLADE SIGNS PRIVATE STREETS

COTTAGE GROVE, MINNESOTA

JANUARY 2022

PLATE NO.

**STR-30**